



HI1975G

Induction cooktop

General description

HI1975G

Available colour: Black

Connection rating: 11100 W

Product dimensions (HxWxD): 4,3 × 90,4 × 52,2 cm

Real Bridge Induction, Auto pan detection, Pause Function



**Real Bridge
Induction**



Auto pan detection



Pause Function

Construction & Performance

- Connection rating: 11100 W
- Consumption in standby mode: 0,5 W
- Middle front: 3,7 kW, 120 mm (Min pot size to be detected), Right front: 3,7 kW, 120 mm (Min pot size to be detected), Middle back: 3,7 kW, 120 mm (Min pot size to be detected), Right back: 3,7 kW, 120 mm (Min pot size to be detected), Left: Ø 26 cm, 5,5 kW, 120 mm (Min pot size to be detected)

Interaction & Control

- SmartControl

Programs, options and modes

- Auto programs: Auto Programs

Design & Integration

- Aluminium black edges
- Niche dimensions (HxWxD): 5,3 × 86 × 49 cm
- Air gap: 40 mm

Technical data

- Connection rating: 11100 W
- Voltage: 220-240 V
- Frequency: 50-60 Hz

Dimensions

- Product dimensions (HxWxD): 4,3 × 90,4 × 52,2 cm
- Net weight: 14,7 kg

Logistic information

- Dimensions of packed product (HxWxD): 14 × 107 × 61 cm
- Gross weight: 16,8 kg
- Product code: 463150
- EAN code: 3838942581090

