

Technical Data Sheet

GENERAL INFORMATION

CORE	Stone Based Hybrid Vinyl
LENGTH	1235mm
WIDTH	178mm
THICKNESS	5.5mm (inc 1mm IXPE)
WEAR LAYER	0.30mm
SURFACE	Natural Wood Look
GLOSS LEVEL	5-8%
COATING	UV coating
ANTI MICROBIAL SURFACE	Yes
BEVEL	Cut bevel
UNIQUE PLANKS	10

PACKAGING

PLANKS / PACK	10
PACK SIZE	2.19m ²
PACK WEIGHT	21.10Kg

MOULDINGS

MATCHING SCOTIA	15 x 28 x 2400 mm
MATCHING T-MOULD	10.5 x 45 x 2400 mm

INSTALLATION

APPLICATION	Residential
JOINING SYSTEM	Tight Lock
INSTALLATION TYPE	Floating
EXPANSION GAP	6mm
ADDITIONAL UNDERLAY	Not allowed
EMBEDDED UNDERFLOOR HEATING	Allowed

TECHNICAL DATA

WEAR RESISTANCE	EN 13329 / ≥2000 cycles (AC3)
IMPACT RESISTANCE	EN 13329 Annex A / ≥1600mm
INDENTATION RESISTANCE	ISO 24343-1 / ≤0.1mm
SLIP RESISTANCE	AS 4586-2103 / P3
REACTION TO FIRE	EN 13501 / Class Bfl -S1
AIRBORNE SOUND INSULATION	Rw 67db
IMPACT SOUND INSULATION	Ln,w 43db
IMPROVED IMPACT SOUND INSULATION	ΔLw 19dB

CERTIFICATIONS

GREENGUARD GOLD	Certified
IAC GOLD	Certified
PRODUCT HEALTH DECLARATION	Platinum level
ASSURE	Certified
HAZARDOUS MINERALS	Silica free

WARRANTIES

RESIDENTIAL	25 Years
LIGHT COMMERCIAL	5 Years
COMMERCIAL	Not applicable

