

Technical Data Sheet

GENERAL INFORMATION	
CORE	Stone Based Hybrid Vinyl
LENGTH	1620mm
WIDTH	225mm
THICKNESS	6.5mm (inc 1mm IXPE)
WEAR LAYER	0.55mm
SURFACE	Synchronised Embossed in Register Texture
GLOSS LEVEL	3-4%
COATING	Shadetech Coating
ANTI MICROBIAL SURFACE	Yes
BEVEL	Micro Bevel on 4 Sides
UNIQUE PLANKS	8

PACKAGING	
PLANKS / PACK	5
PACK SIZE	1.82m ²
PACK WEIGHT	21.25Kg

MOULDINGS	
MATCHING SCOTIA	15 x 28 x 2400 mm
MATCHING T-MOULD	10.5 x 45 x 2400 mm

INSTALLATION	
APPLICATION	Residential & Commercial
JOINING SYSTEM	Tight Lock
INSTALLATION TYPE	Floating
EXPANSION GAP	6mm
ADDITIONAL UNDERLAY	Not allowed
EMBEDDED UNDERFLOOR HEATING	Allowed

TECHNICAL DATA	
WEAR RESISTANCE	EN 13329 / ≥4000 cycles (AC4)
IMPACT RESISTANCE	EN 13329 Annex A / ≥1600mm
INDENTATION RESISTANCE	ISO 24343-1 / ≤0.1mm
SLIP RESISTANCE	AS 4586-2103 / P4
REACTION TO FIRE	EN 13501 / Class Bfl -S1
AIRBORNE SOUND INSULATION	Rw 67db
IMPACT SOUND INSULATION	Ln,w 43db
IMPROVED IMPACT SOUND INSULATION	ΔLw 19dB

CERTIFICATIONS	
GREENGUARD GOLD	Certified
IAC GOLD	Certified
PRODUCT HEALTH DECLARATION	Platinum Level
ASSURE	Certified
HAZARDOUS MINERALS	Silica free

WARRANTIES	
RESIDENTIAL	Lifetime
LIGHT COMMERCIAL	15 Years
COMMERCIAL	15 Years

