

COLOUR CHANGEABLE DOWNLIGHT AND SHOP LIGHTER

1 ON & 2 OFF= WW 3000K / 1 OFF & 2 ON= CW 5000K/ 1 ON & 2 ON = NW 4000K

VEET APPROVED #: 5609

Key Features

- Dimmable on Leading Edge, Trailing Edge, Universal 3-100% also C-Bus & Dynalite Systems.
- Colour temperature changeable on back of downlight.
- IP44 Rated for indoors use and bathrooms.
- Frosted lens to decrease the glare.
- Power factor 0.95.
- IC-F certified; can be covered with normal building material without thermal risk
- Flex in plug.



AU08-DL20W/W/BS
AU08-DL30W/W/BS
AU08-DL40W/W/BS



AU08-DL45W/W/BS

AU01-DLR40W/W/BS


Applications

- Shopping Centres, Hotels, Restaurants, Homes, Show Rooms, etc.


TECHNICAL SPECIFICATIONS

Model.	LED Type	LED Q'ty (pcs)	Colour Temperature	Voltage (V)	Beam Angle	Wattage (W)	Luminosity (lm)	CRI(Ra)	Frame colour	Warranty	IP RATING	Dimmable
AU08-DL20W/W/BS	SMD2835	96pcs	3K 4K 5K	200~240v	120°	20W	2030-2080lm	80	White	3 years	IP44	Yes
AU08-DL30W/W/BS	SMD2835	144pcs	3K 4K 5K	200~240v	120°	30W	3030-3080lm	80	White	3 years	IP44	Yes
AU08-DL40W/W/BS	SMD2835	196pcs	3K 4K 5K	200~240v	120°	40W	4030-4080lm	80	White	3 years	IP44	Yes
AU08-DL45W/W/BS	SMD2835	210pcs	3K 4K 5K	200~240v	80°	45W	4500-4950lm	80	White	3 years	IP44	Yes
AU01-DLR40W/W/BS	SMD3030	96pcs	3K 4K 5K	200~240v	120°	40W	3630-3680lm	80	White	3 years	IP44	Yes


Product Dimension: (mm)




AU08-DL20W/W/BS
AU08-DL30W/W/BS



AU08-DL40W/W/BS



AU08-DL45W/W/BS



AU01-DLR40W/W/BS

PACKING DETAILS:

Product: AU08-DL20W/W/BS
AU08-DL30W/W/BS

Net Weight: 0.89kg
Inner box size: 260*225*65mm
Outer ctn size: 465*450*270mm
Q'ty per ctn: 14 pcs
G.W per ctn: 16.5 kg

Product: AU08-DL40W/W/BS

Net Weight: 1.18 kg
Inner box size: 290*260*65mm
Outer ctn size: 540*480*320mm
Q'ty per ctn: 14 pcs
G.W per ctn: 20.5 kg

Product: AU08-DL45W/W/BS

Net Weight: 2.05 kg
Inner box size: 315*315*155mm
Outer ctn size: 660*340*500mm
Q'ty per ctn: 6 pcs
G.W per ctn: 14.27 kg

Product: AU01-DLR40W/W/BS

Net Weight: 1.90 kg
Inner box size: 245*153*115mm
Outer ctn size: 548*390*395mm
Q'ty per ctn: 8 pcs
G.W per ctn: 16.2 kg