



LGR DEHUMIDIFIER

Low Grain Refrigerant

Developed to excel in even the toughest water damage restoration environments, the professional grade **XPOWER LGR Dehumidifier** extracts more moisture than much larger commercial models. Features '**Dual Intake Technology**' which boosts efficiency and performance in a wide range of operating conditions. Designed to maximise storage space, these compact units **stack up to 3 high** and features **2 molded handle grip points** on the front and back. For added mobility, this model also comes with **wheels and handle** for easy transport. A user friendly **digital control panel** monitors your job site's current humidity and records operating time. Also features an **auto purge pump with drainage hose** that automatically purges when full, eliminating the task of monitoring collection tank levels.

Model	XD-85LH With wheels and mobility handle	
Moisture Removal Capacity	85 pints / 41 L /day at AHAM (80°F/27°C, 60% RH) 145 pints / 69 L /day at Saturation (90°F/32°C, 90% RH)	
Volts/Hertz	220-240V / 50Hz	
Amps	3.7A	
Rated Airflow	306 m³/h	
Speed	Automatic Speed Control	
Filter Type	Washable Stainless Steel Filter	
Cord Length	7.6 metres	
Drain Hose	12.2 metres	
Operating Range	33°- 105°F (0.6°- 40.6°C)	
Unit Weight	30.5kg	
Unit Size	33.3 x 70.6 x 59.5cm	
Stackable	Up to 3 units high	



CONTACT CLEANSTAR FOR YOUR NEAREST STOCKIST

☎ (03) 9460 5655

@ sales@cleanstar.com.au

☎ (03) 9460 5666

🌐 cleanstar.com.au

