

N 70
D58ML66N1
86 CM FULLY INTEGRATED RANGEHOOD



COOKING PASSION SINCE 1877



The integrated rangehood: offers a sleek and seamless design in the kitchen with fully integrated installation.

- ✓ Extraction rate: at 800 m³/h, it quickly ensures optimal kitchen air quality.
- ✓ LED lighting: for perfect, energy-efficient illumination of the cooktop.
- ✓ Intensive speed setting with reset: automatically resets the hood to regular speed setting after 6 min.

Features

Technical Data

Typology : Traditional
Approval certificates : CE, VDE
Length electrical supply cord (cm) : 150
Required niche size for installation (HxWxD) : 418mm x 836mm x 264mm
Minimum distance above an electric hob : 500
Minimum distance above a gas hob : 650
Net weight (kg) : 12.756
Type of control : Electronic
Maximum output air extraction (m³/h) : 610
Boost position output recirculating (m³/h) : 380
Maximum output recirculating air (m³/h) : 310
Boost position air extraction (m³/h) : 800
Number of lights : 2
Noise level (dB) : 64
Diameter of air outlet (mm) : 150 / 120
Grease filter material : Washable aluminium
EAN code : 4242004238300
Connection Rating (W) : 172
Current (A) : 3
Voltage (V) : 220-240
Frequency (Hz) : 50
Plug type : Gurdy plug w/ earthing
Installation typology : Built-in

Optional accessories

Z5135X1	Active carbon filter
Z5135X3	Recirculating kit



4 242004 238300

N 70

D58ML66N1

86 CM FULLY INTEGRATED RANGEHOOD

Features

Design & Innovation

- For installation in a kitchen cabinet
- Appliance colour: Stainless steel
- Rim ventilation
- metal grease filters with stainless steel cover

Power and Mode of Operation

- Electronic controls
- Push button controls (3 power levels plus intensive setting) with Electronic display
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 610 m³/h
Intensive 800 m³/h
- Noise min./max. Normal Level: 41/64 dB
Noise max. Intensive setting: 70 dB
- Suitable for ducted extraction and recirculation
- Accessories required for recirculated extraction: Recirculating kit

Comfort & Convenience

- Automatic intensive revert setting - 6 min
- Automatic run on for Automatic run on time - 30 min
- Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:
Max. normal use: 64 dB(A) re 1 pW (51 dB(A) re 20 µPa sound pressure)
Intensive: 70 dB(A) re 1 pW (57 dB(A) re 20 µPa sound pressure)
- EfficientDrive BLDC technology
- 2 x 1 Watt LED lights
- Dishwasher safe metal grease filters
- Saturation indicator for grease filters

Technical Information

- Built-in dimensions: width: 84 cm, depth: 26 cm
- Dimensions exhaust air (HxWxD): 418-418 x 860 x 300 mm
- 120 or 150 mm tube connection diameter
- Power rating: 172 W
- Average Energy Consumption: 25.5 kWh/year
- Electrical cable length 1.5 m

N 70
 D58ML66N1
 86 CM FULLY INTEGRATED RANGEHOOD

Dimensioned drawings

